

View Online at <https://aerobasegroup.com/nsn/6625-00-858-4583>

Circuit Current For Which Designed:

Ac

Overall Diameter:

Between 1.993 inches and 2.000 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

0.5 amperes

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 2.287 inches and 2.307 inches

Meter Body Diameter Behind Mounting Flange:

Between 1.923 inches and 1.937 inches

Movement Type:

Moving iron vane

Scale Marking:

De-icer empennage; ok; faulty

Mounting Facility Type And Quantity:

1 clamp

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

1 connector, receptacle

Special Markings:

Ok band from 0 to .36 amp deflection; faulty band from .36 to .5

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0