

View Online at <https://aerobasegroup.com/nsn/6625-00-859-5063>

Circuit Current For Which Designed:

Dc

Overall Length:

2.580 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.670 inches

Overall Height:

3.940 inches

Overall Width:

4.250 inches

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Nut 10; washer 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.110 inches

Meter Body Diameter Behind Mounting Flange:

3.250 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges and red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-10.0/+0.0 decibels single indicator 1st range

Mounting Stud Diameter:

0.138 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Zero pos r-h of scale

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

175 ohms internal res

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0