

View Online at <https://aerobasegroup.com/nsn/6625-00-859-5063>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.580 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.670 inches

**Overall Height:**

3.940 inches

**Overall Width:**

4.250 inches

**Mounting Stud Length:**

0.500 inches

**Furnished Items And Quantity:**

Nut 10; washer 8

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

500.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.110 inches

**Meter Body Diameter Behind Mounting Flange:**

3.250 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges and red single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

-10.0/+0.0 decibels single indicator 1st range

**Mounting Stud Diameter:**

0.138 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Zero pos r-h of scale

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

175 ohms internal res

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0