NSN 6625-00-860-7306

Voltmeter - Page 1 of 2

Ac

Overall Length: 1.750 inches

Mounting Hole Diameter:

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-860-7306

0.15625 inches
Scale Division Quantity:
28 single indicator single range
Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.160 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.390 inches
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.760 inches
2.760 inches
2.760 inches Movement Type:
2.760 inches Movement Type: Moving iron vane
2.760 inches Movement Type: Moving iron vane Background Color:
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color:
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity:
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Scale Graduation Type:
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Scale Graduation Type: Linear single indicator single range
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Scale Graduation Type: Linear single indicator single range Measurement Range:
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+150.0 volts, ac single indicator single range
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method:
2.760 inches Movement Type: Moving iron vane Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal

NSN 6625-00-860-7306

Voltmeter - Page 2 of 2



Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Markings:
Elongated graduation mark at 120.0 v
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0