

View Online at <https://aerobasegroup.com/nsn/6625-00-868-6927>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2000.0

Reliability Indicator:

Not established

Overall Length:

Between 3.350 inches and 3.410 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.020 inches and 3.060 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 2.650 inches and 2.690 inches

Overall Height:

Between 3.930 inches and 3.960 inches

Overall Width:

Between 4.240 inches and 4.260 inches

Mounting Stud Length:

Between 0.490 inches and 0.510 inches

Furnished Items And Quantity:

Nut 14; washer 14

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

13.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 1.520 inches and 1.540 inches

Meter Body Diameter Behind Mounting Flange:

Between 3.240 inches and 3.260 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+500.0 amperes, rf single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Nonglare glass and self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 4 threaded stud

Operating Voltage Rating In Volts:

6.0 dc

Special Features:

Two mazda no. 47 lamps required

Material:

Plastic phenol-formaldehyde

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Two lugs and term. For lamps; two term. For meter

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0