

View Online at <https://aerobasegroup.com/nsn/6625-00-869-8734>

Circuit Current For Which Designed:

Dc

Overall Length:

4.400 inches

Mounting Hole Diameter:

0.112 inches

Scale Division Quantity:

2 single indicator single range

Overall Diameter:

3.510 inches

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

Between 3.150 inches and 3.170 inches

Furnished Items And Quantity:

Nut 7; washer 9

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.250 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+380.0/+420.0 hertz single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Stamp iaw mil-std-103

Style Designator:

Round flush mtg

Supplementary Features:

Line voltage 105.0 to 130.0 vac; power consumption 3 va max

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0