

View Online at <https://aerobasegroup.com/nsn/6625-00-869-8734>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

4.400 inches

**Mounting Hole Diameter:**

0.112 inches

**Scale Division Quantity:**

2 single indicator single range

**Overall Diameter:**

3.510 inches

**Environmental Protection:**

Humidity resistant and shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

Between 3.150 inches and 3.170 inches

**Furnished Items And Quantity:**

Nut 7; washer 9

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.250 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+380.0/+420.0 hertz single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Stamp iaw mil-std-103

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Line voltage 105.0 to 130.0 vac; power consumption 3 va max

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0