NSN 6625-00-872-0982

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-872-0982

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.404 inches
Mounting Hole Diameter:
0.145 inches
Overall Diameter:
4.506 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
4.130 inches
Furnished Items And Quantity:
Nut 8; lockwasher 8; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Six hole/stud bolt circle
Sensitivity Rating:
10.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.225 inches
Meter Body Diameter Behind Mounting Flange:
3.600 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range

Scale Marking:

O; 1; 2; 3; 4; 5; 6; 7; 8; 9; 10; check

Mounting Facility Type And Quantity:

6 screw and 6 unthreaded hole

NSN 6625-00-872-0982

Special Scale Meter - Page 2 of 2



Scale Graduation Type:
Nonlinear single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On front, check; microhos-cm 3; on back, sealed d0 not open
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Chromate
Special Test Features:
Complies with mil-m-10304
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0