

View Online at <https://aerobasegroup.com/nsn/6625-00-876-9625>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

Between 2.340 inches and 2.480 inches

**Mounting Stud Length:**

Between 0.550 inches and 0.590 inches

**Overall Diameter:**

Between 2.280 inches and 2.320 inches

**Distance Between Mounting Facility Centers:**

1.320 inches

**Furnished Items And Quantity:**

Nut 3; washer 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

Between 1.500 inches and 1.540 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 2.030 inches and 2.090 inches

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 clamp and 2 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+18.0/+33.0 volts single indicator single range

**Mounting Stud Diameter:**

0.190 inches

**Circuit Attachment Method And Quantity:**

3 threaded stud

**Special Features:**

Rubber gasket

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0