

View Online at <https://aerobasegroup.com/nsn/6625-00-876-9625>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 2.340 inches and 2.480 inches

Mounting Stud Length:

Between 0.550 inches and 0.590 inches

Overall Diameter:

Between 2.280 inches and 2.320 inches

Distance Between Mounting Facility Centers:

1.320 inches

Furnished Items And Quantity:

Nut 3; washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 1.500 inches and 1.540 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.030 inches and 2.090 inches

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+18.0/+33.0 volts single indicator single range

Mounting Stud Diameter:

0.190 inches

Circuit Attachment Method And Quantity:

3 threaded stud

Special Features:

Rubber gasket

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0