

View Online at <https://aerobasegroup.com/nsn/6625-00-877-6105>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

6.400 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

40 single indicator single range

**Overall Diameter:**

3.510 inches

**Environmental Protection:**

Cold resistant and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Mounting Bolt Circle Diameter:**

3.220 inches

**Furnished Items And Quantity:**

Nut 7; lockwasher 3; flat washer 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+380.000/+420.000 hertz

**Sensitivity Rating:**

120.0 volts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-0.2/+0.2 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

4.380 inches

**Meter Body Diameter Behind Mounting Flange:**

2.860 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+380.0/+420.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Operating Voltage Rating In Volts:**

Between 105.0 ac and 135.0 ac

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Cadmium

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Round flush mtg

**Unit Of Issue Weight:**

2.00 pounds

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0