NSN 6625-00-878-4688

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-878-4688

Circuit Current For Which Designed:
Ac
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
1 flange and 3 unthreaded hole

Measurement Range:

Scale Graduation Type:

Linear single indicator single range

+0.0/+50.0 volts, ac single indicator single range

NSN 6625-00-878-4688 Voltmeter - Page 2 of 2



Scale Selection Method:
Switch
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud and 2 solder lug
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/6 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A310a0
No Fiig: A310a0