

View Online at <https://aerobasegroup.com/nsn/6625-00-880-1211>

Vibration Resistance Range In Hertz:

+10.0/+50.0

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

-0.0/+55.0 degrees celsius

Average Life Measurement:

Not rated

Maximum Operating Altitude Rating:

Not rated

Installation Design:

Portable

Circuit Construction Type:

Any acceptable

Frequency Per Channel:

20.0 hertz operating channel err-100

Frequency Adjustment Type:

Continuous

Attenuation In Decibels:

50.0

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms output channel

Pulse Duration Per Channel:

60.000 nanoseconds output channel err-100

Pulse Rise Time Per Channel:

15.000 nanoseconds output channel

Polarity Per Channel:

Positive output channel err-100

Pulse Repetition Rate Per Channel:

20.000 pulses per second operating channel err-100

Pulse Peak Amplitude Per Channel:

50.000 volts output channel

Maximum Continuous Operating Time In Hours:

Not rated

Operating Ac Frequency In Hertz:

50.0 single voltage

External Ac Operating Voltage In Volts:

230.0 single voltage

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32200