NSN 6625-00-880-1620

Circuit Current For Which Designed:

Ac

Overall Length: 4.09375 inches

0.150 inches

Mounting Hole Diameter:

Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-880-1620

Frequency Rating:
400.0 hertz
Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Term. Hdw 2
Indicator Type:
Vibrating reed
Installation Design:
Panel
Register Quantity:
1
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+10.000/+600.000 hertz
D (D 10 d)
Resonant Reed Quantity:
11
•
11
11 Meter Depth Behind Mounting Flange:
11 Meter Depth Behind Mounting Flange: 3.3125 inches
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange:
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type:
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed Power Source:
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed Power Source: External
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed Power Source: External Mounting Facility Type And Quantity:
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed Power Source: External Mounting Facility Type And Quantity: 3 unthreaded hole
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed Power Source: External Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed Power Source: External Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +360.0/+440.0 hertz single indicator single range
Meter Depth Behind Mounting Flange: 3.3125 inches Meter Body Diameter Behind Mounting Flange: 2.78125 inches Movement Type: Vibrating reed Power Source: External Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +360.0/+440.0 hertz single indicator single range Scale Selection Method:

NSN 6625-00-880-1620

Electrical Frequency Meter - Page 2 of 2



Operating Voltage Rating In Volts:
Between 100.0 ac and 150.0 ac
Phase:
Single
Special Features:
Ruggedized
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0