

View Online at <https://aerobasegroup.com/nsn/6625-00-880-1962>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.337 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.600 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches

Overall Height:

0.500 inches

Overall Width:

1.250 inches

Mounting Hole Diameter:

0.101 inches

Scale Division Quantity:

6 single indicator single range

Environmental Protection:

Cold resistant and fungus proof and heat resistant and salt spray resistant and shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

Seven vertical graduation marks

Mounting Facility Type And Quantity:

2 bracket and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0