NSN 6625-00-880-4982

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-880-4982

View Online at https://aerobasegroup.com/nsn/6625-00-880-4982
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
2000.0
Overall Length:
3.455 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches
Overall Height:
4.422 inches
Overall Width:
4.422 inches
Scale Division Quantity:
60 single indicator single range
Mounting Stud Length:
0.750 inches
Environmental Protection:
Dust resistant
Furnished Items And Quantity:
Hex nuts 6; flat washers 6
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
100.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.5/+1.5 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.815 inches
Meter Body Diameter Behind Mounting Flange:
3.960 inches
Movement Type:
Moving coil, permanent magnet

White single indicator single range

Background Color:

NSN 6625-00-880-4982

Ammeter - Page 2 of 2

A310a0



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
15.0/+15.0 amperes, dc single indicator single range
Mounting Stud Diameter:
0.250 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Oc amperes
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint lusterless
Style Designator:
Rectangular flush mtg
Test Data Document:
31349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fila: