

View Online at <https://aerobasegroup.com/nsn/6625-00-881-0936>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

1.925 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

10 single indicator 2nd range

Overall Diameter:

2.695 inches

Environmental Protection:

Dust resistant and water resistant

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.025/+16.000 kilohertz

Dial Scale Marking Color:

Black single indicator 2nd range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.140 inches

Meter Body Diameter Behind Mounting Flange:

2.150 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Buff single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

-20.0/+3.0 voice units single indicator 1st range

Features Provided:

Knife edge pointer and magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solderless lug

Special Markings:

First scale black on minus, red on plus; sealed do not open

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304 type mr26

Style Designator:

Round flush mtg

Supplementary Features:

Ref level: 1 mw 600 ohms; resistance: 3900 ohms porm 10 pct

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0