

View Online at <https://aerobasegroup.com/nsn/6625-00-881-0936>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

1.925 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

10 single indicator 2nd range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Dust resistant and water resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+0.025/+16.000 kilohertz

**Dial Scale Marking Color:**

Black single indicator 2nd range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.140 inches

**Meter Body Diameter Behind Mounting Flange:**

2.150 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Buff single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator 1st range

**Measurement Range:**

-20.0/+3.0 voice units single indicator 1st range

**Features Provided:**

Knife edge pointer and magnetic shield

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Special Markings:**

First scale black on minus, red on plus; sealed do not open

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Conforms to mil-m-10304 type mr26

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Ref level: 1 mw 600 ohms; resistance: 3900 ohms porm 10 pct

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0