

View Online at <https://aerobasegroup.com/nsn/6625-00-881-5092>

Circuit Current For Which Designed:

Dc

Overall Length:

2.000 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

40 single indicator single range

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-10.0/+10.0 amperes, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Terminal no. 1/4-28 thd 0.375 in. Lg

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

Mr26w1t1dcaar type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0