

View Online at <https://aerobasegroup.com/nsn/6625-00-881-7727>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.106 inches and 1.118 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.106 inches and 1.118 inches

Overall Height:

Between 1.795 inches and 1.805 inches

Overall Width:

Between 1.795 inches and 1.805 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

3 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 milliamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 unthreaded hole

Measurement Range:

+0.0/+50.0 milliamperes, dc single indicator single range

Features Provided:

Self-illumination facility

Movement Suspension Method:

Metal pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Style Designator:

Rectangular flush mtg

Test Data Document:

81349-mil-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0