NSN 6625-00-883-3284

Wattmeter - Page 1 of 2

Power Source:

External



View Online at https://aerobasegroup.com/nsn/6625-00-883-3284

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.430 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
10 single indicator 1st range
Overall Diameter:
2.695 inches
Environmental Protection:
Cold resistant and dust resistant and fungus resistant and humidity resistant and shock proof and vibration proof and vibration resistant an
water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 5; lockwasher 7; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.900 inches
Meter Body Diameter Behind Mounting Flange:
2.185 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges

NSN 6625-00-883-3284

Wattmeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator 3rd range
Measurement Range:
+0.0/+15000.0 watts single indicator 3rd range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304/5
Surface Treatment Specification:
595 no. 27038 federal standard single treatment response
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0