NSN 6625-00-883-9106

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-883-9106

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.500 inches

Overall Diameter:

3.510 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg hdw 3; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

150.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-00-883-9106

Ammeter - Page 2 of 2



Power Source: External Mounting Facility Type And Quantity: 3 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+1.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.138 inches **Scale Selection Method:** Terminal **Features Provided:** Luminous scale marking and magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solder lug and 2 threaded stud **Special Features:** Ruggedized Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened **Surface Treatment:** Enamel semigloss **Special Test Features:** Meets requirements of mil-m-10304/12 Style Designator: Round flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A310a0