NSN 6625-00-883-9106

Ammeter - Page 1 of 2

3000.0

Overall Length: 2.850 inches

0.500 inches

3.510 inches

Overall Diameter:

Scale Division Quantity:

Mounting Stud Length:

50 single indicator single range

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-883-9106

Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mtg hdw 3; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
150.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range

NSN 6625-00-883-9106

Ammeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
3 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+1.0 milliamperes, dc single indicator single range
Mounting Stud Diameter:
0.138 inches
Scale Selection Method:
Terminal
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Meets requirements of mil-m-10304/12
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0