

View Online at <https://aerobasegroup.com/nsn/6625-00-889-1555>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.000 inches

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 3; screw 3; lockwasher 3

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

3 flange

Measurement Range:

+0.0/+200.0 amperes, dc single indicator single range

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Used with external shunt

Style Designator:

C1 round flush mtg

Test Data Document:

81349-mil-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0