## NSN 6625-00-892-1708

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-892-1708

Overall Length: 2.240 inches Scale Division Quantity: 30 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
2.240 inches  Scale Division Quantity: 30 single indicator single range  Overall Diameter: 2.695 inches  Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color: White single indicator single range  Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.860 inches  Meter Body Diameter Behind Mounting Flange: 2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color: Black single indicator single range  Mounting Facility Type And Quantity: 3 flange  Measurement Range: -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method: Jewel pivot base
Scale Division Quantity: 30 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Overall Diameter:  2.695 inches  Mounting Bolt Circle Diameter:  2.440 inches Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
2.695 inches  Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Mounting Bolt Circle Diameter:  2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  White single indicator single range  Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.860 inches  Meter Body Diameter Behind Mounting Flange: 2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity: 3 flange  Measurement Range: -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method: Jewel pivot base
Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.860 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
White single indicator single range  Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.860 inches  Meter Body Diameter Behind Mounting Flange: 2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity: 3 flange  Measurement Range: -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.860 inches  Meter Body Diameter Behind Mounting Flange:  2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.860 inches  Meter Body Diameter Behind Mounting Flange:  2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Meter Depth Behind Mounting Flange:  1.860 inches  Meter Body Diameter Behind Mounting Flange:  2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
1.860 inches  Meter Body Diameter Behind Mounting Flange: 2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity: 3 flange  Measurement Range: -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Meter Body Diameter Behind Mounting Flange:  2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
2.210 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Movement Type:  Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Moving coil, permanent magnet  Background Color:  Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Black single indicator single range  Mounting Facility Type And Quantity:  3 flange  Measurement Range:  -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Mounting Facility Type And Quantity: 3 flange Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
3 flange  Measurement Range: -30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Measurement Range: -30.0/+30.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
-30.0/+30.0 amperes, dc single indicator single range  Movement Suspension Method:  Jewel pivot base
Movement Suspension Method:  Jewel pivot base
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Charge and discharge
Style Designator:
C1 round flush mtg
Shelf Life:

N/a

## NSN 6625-00-892-1708

Ammeter - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0