# NSN 6625-00-892-2470

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-892-2470

Circuit Current For Which Designed: Ac Dielectric Withstanding Voltage In Volts: 3000.0 Overall Length: 2.650 inches Mounting Hole Diameter: Between 0.120 inches and 0.130 inches Scale Division Quantity:
Dielectric Withstanding Voltage In Volts: 3000.0 Overall Length: 2.650 inches Mounting Hole Diameter: Between 0.120 inches and 0.130 inches
3000.0 Overall Length: 2.650 inches Mounting Hole Diameter: Between 0.120 inches and 0.130 inches
Overall Length: 2.650 inches Mounting Hole Diameter: Between 0.120 inches and 0.130 inches
2.650 inches <b>Mounting Hole Diameter:</b> Between 0.120 inches and 0.130 inches
Mounting Hole Diameter: Between 0.120 inches and 0.130 inches
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Dustproof
Mounting Bolt Circle Diameter:
2.440 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+720.000/+880.000 hertz
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.250 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
3 unthreaded hole

## NSN 6625-00-892-2470

Ammeter - Page 2 of 2



Scale Graduation Type:

Linear single indicator single range

#### **Measurement Range:**

+0.0/+50.0 milliamperes, ac single indicator single range

#### **Scale Selection Method:**

Terminal

**Features Provided:** 

Magnetic shield

**Movement Suspension Method:** 

Taut band

**Circuit Attachment Method And Quantity:** 

2 threaded stud

Material:

Steel

**Nuclear Hardness Critical Feature:** 

Nonhardened

**Style Designator:** 

Round flush mtg

#### **Test Data Document:**

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A310a0