NSN 6625-00-892-4546

Ammeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-892-4546

Circuit Current For Which Designed:
Dc
Overall Length:
2.240 inches
Overall Diameter:
2.695 inches
Mounting Bolt Circle Diameter:
2.440 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
150.0 millivolts
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.860 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Moving coil, permanent magnet
Moving coil, permanent magnet Mounting Facility Type And Quantity:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Style Designator:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: C1 round flush mtg
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: C1 round flush mtg Shelf Life:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: C1 round flush mtg Shelf Life: N/a
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: C1 round flush mtg Shelf Life: N/a Unit Of Measure:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: C1 round flush mtg Shelf Life: N/a Unit Of Measure:
Moving coil, permanent magnet Mounting Facility Type And Quantity: 3 flange Measurement Range: +0.0/+100.0 microamperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Style Designator: C1 round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: