

View Online at <https://aerobasegroup.com/nsn/6625-00-892-5251>

Current Type:

Ac

Frequency Rating:

50.0 hertz and 60.0 hertz and 400.0 hertz

Accessory Components And Quantity:

Cable assembly 1; cover storage 1; lead ground 1, probe voltage divider 2; tip probe set 1

Voltage Rating:

115.0 pounds per hour wet and 230.0 pounds per hour wet

Beam Quantity:

1

Graduation Interval:

Any acceptable

Mounting Method:

Cabinet

Accuracy Range In Percent:

-3.0/+3.0

Screen Size:

5.000 in.

Sweep Circuits:

Not included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 megahertz and 40.0 megahertz

Y-axis Frequency Response Rating:

Between 0.0 megahertz and 5.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g