NSN 6625-00-893-9796

Modulation Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-893-9796

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.067 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
25 single indicator all ranges
Overall Diameter:
3.500 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Nut 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
50.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.405 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External

NSN 6625-00-893-9796

Modulation Meter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0/+2.5 percent modulation single indicator 2nd range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized per mil-m-10304
Special Markings:
Pct amplitude modulation
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0