NSN 6625-00-894-2827

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-894-2827

| Circuit Current For Which Designed: |
|---|
| |
| Dielectric Withstanding Voltage In Volts: |
| |
| Overall Length: |
| 2.650 inches |
| Mounting Hole Diameter: |
| 0.125 inches |
| Scale Division Quantity: |
| 10 single indicator single range |
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| 2.220 inches |
| Furnished Items And Quantity: |
| Lockwasher 3, nut 3, screw 3 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| White single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.600 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.210 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| Black single indicator single range |
| Pointer Color: |
| White single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |

Linear single indicator single range

NSN 6625-00-894-2827

Ammeter - Page 2 of 2



Measurement Range:

+0.0/+50.0 microamperes, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-10304/5 government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0