

View Online at <https://aerobasegroup.com/nsn/6625-00-897-4970>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Overall Length:**

3.310 inches

**Scale Division Quantity:**

30 single indicator single range

**Mounting Stud Length:**

0.500 inches

**Overall Diameter:**

2.700 inches

**Environmental Protection:**

Dust resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Washers 3, nuts 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.470 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+14.2/+15.7 volts, dc single indicator single range

**Mounting Stud Diameter:**

0.125 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

3 solderless lug

**Special Features:**

Rf ground terminal

**Special Markings:**

Green band from 14.7 to 15.3 volts

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round semi-flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0