

View Online at <https://aerobasegroup.com/nsn/6625-00-897-5248>

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Voltage Rating:**

Between 105.0 volts and 125.0 volts

**Accuracy Range In Percent:**

-3.0/+3.0

**Screen Size:**

5 in.

**Sweep Circuits:**

Included

**Sweep Circuit Type:**

Horizontal and vertical

**Single Trigger Sweep Duration:**

Between 2.0 seconds and 0.2 microseconds

**Trigger Sweep Polarity Switch:**

Included

**Expanded Sweep:**

Provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 0.0 megahertz and 15.0 megahertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Amplitude Calibrating Voltage Waveform:**

Square wave

**Calibrating Peak To Peak Amplitude:**

1.0 volts

**Measurement Range Quantity:**

3

**Measurement Range Steps:**

0.05 to 20v per cm

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T320-g