

View Online at <https://aerobasegroup.com/nsn/6625-00-897-5248>

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Voltage Rating:

Between 105.0 volts and 125.0 volts

Accuracy Range In Percent:

-3.0/+3.0

Screen Size:

5 in.

Sweep Circuits:

Included

Sweep Circuit Type:

Horizontal and vertical

Single Trigger Sweep Duration:

Between 2.0 seconds and 0.2 microseconds

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 megahertz and 15.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

1.0 volts

Measurement Range Quantity:

3

Measurement Range Steps:

0.05 to 20v per cm

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g