## NSN 6625-00-903-0540

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-903-0540

Circuit Current For Which Designed:
Dc
Overall Length:
3.455 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches
Overall Height:
4.422 inches
Overall Width:
4.422 inches
Scale Division Quantity:
50 single indicator single range
Mounting Stud Length:
1.500 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Four hole/stud rectangular/square  Sensitivity Rating:
Sensitivity Rating:
Sensitivity Rating: 100.0 millivolts
Sensitivity Rating: 100.0 millivolts  Dial Scale Marking Color:
Sensitivity Rating: 100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range
Sensitivity Rating: 100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches  Meter Body Diameter Behind Mounting Flange:
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches  Meter Body Diameter Behind Mounting Flange:  3.960 inches
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches  Meter Body Diameter Behind Mounting Flange:  3.960 inches  Movement Type:
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches  Meter Body Diameter Behind Mounting Flange:  3.960 inches  Movement Type:  Moving coil, permanent magnet
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches  Meter Body Diameter Behind Mounting Flange:  3.960 inches  Movement Type:  Moving coil, permanent magnet  Background Color:
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches  Meter Body Diameter Behind Mounting Flange:  3.960 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range
Sensitivity Rating:  100.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.815 inches  Meter Body Diameter Behind Mounting Flange:  3.960 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Pointer Color:

4 threaded stud

**Mounting Facility Type And Quantity:** 

## NSN 6625-00-903-0540

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-25.0/+25.0 amperes, $$ dc single indicator single range
Mounting Stud Diameter:
0.250 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic
<b>Nuclear Hardness Critical Feature:</b>
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0