NSN 6625-00-903-8095

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-903-8095

Reliability Indicator:
Not established
Overall Length:
2.850 inches
Mounting Hole Diameter:
0.166 inches
Overall Diameter:
3.510 inches
Mounting Bolt Circle Diameter:
3.160 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.800 inches
2.800 inches
2.800 inches Movement Type:
2.800 inches Movement Type: Moving iron vane
2.800 inches Movement Type: Moving iron vane Background Color:
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity:
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity:
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature:
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature: Nonhardened
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature: Nonhardened Style Designator:
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg
2.800 inches Movement Type: Moving iron vane Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Fsc Application Data:

NSN 6625-00-903-8095

Ammeter - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0