NSN 6625-00-905-7160

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-905-7160

Circuit Current For Which Designed:
Dc
Overall Length:
2.010 inches
Mounting Hole Diameter:
0.155 inches
Scale Division Quantity:
20 single indicator all ranges
Overall Diameter:
3.468 inches
Mounting Bolt Circle Diameter:
3.156 inches
Furnished Items And Quantity:
Nut 2; washer
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
Sensitivity rating.
20.0 microamperes
20.0 microamperes
20.0 microamperes Dial Scale Marking Color:
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent:
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange:
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange:
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches Movement Type:
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches Movement Type: Moving coil, permanent magnet
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches Movement Type: Moving coil, permanent magnet Background Color:
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color:
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color: Black single indicator all ranges
20.0 microamperes Dial Scale Marking Color: Black single indicator all ranges and green single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.265 inches Meter Body Diameter Behind Mounting Flange: 2.794 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color: Black single indicator all ranges Scale Marking:

Scale Graduation Type:

Linear single indicator all ranges

NSN 6625-00-905-7160 Special Scale Meter - Page 2 of 2



Features Provided:
Zero adjuster
Criticality Code Justification:
Feat
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Weapon system essential
Special Markings:
Green band from 1100 to 1400
Material:
Steel
Surface Treatment:
Enamel
Style Designator:
C1 round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A310a0