

View Online at <https://aerobasegroup.com/nsn/6625-00-914-3619>

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**End Application:**

F-16 a, b, c, d support equipment

**Electrical Connection Type:**

Bnc

**Accessory Controlling Agency:**

Any acceptable

**Internal Battery Accommodation:**

Not included

**Voltage Rating:**

115.0 volts or 230.0 volts

**Electrical Connection Quantity:**

2

**Accessory Component Name:**

Any acceptable

**Measurement Type:**

Frequency and ratio and period average

**Frequency Range:**

+0.100/+50.000 megahertz multiple period and +0.000/+10.000 megahertz multiple period and +0.000/+1.000 megahertz multiple period and +0.000/+1.000 megahertz multiple period and +0.000/+0.300 megahertz multiple period

**Accuracy Rating:**

Porm 1 count porm 1 count of f1, porm trigger error of f2 porm 1 count and porm trigger error

**Gate Time:**

10.0 seconds

**Sensitivity Rating:**

Any acceptable

**Ratio Display:**

F1/f2 times period multiplier

**Period Range:**

+1.0/+100000.0

**Internal Calibration Feature:**

Included

**Display Type:**

Any acceptable

**Display Units Indicator:**

Not included

**Display Positioned Decimal Point:**

Not provided

**Display Storage Facility:**

Included

**Remote Control Provisions:**

Not included

**Solid State Feature:**

Not included

**Inclosure Material And Location:**

Metal case

**Inclosure Surface Treatment And Location:**

Enamel case

**Plug-in Units Provision:**

Included

**Standard Frequency Output Feature:**

Included

**Phase:**

Single

**Specification Or Standard:**

4 type

**Fsc Application Data:**

Counter type indicators, test, digital display

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fii:**

T297-a