

View Online at <https://aerobasegroup.com/nsn/6625-00-914-3619>

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

End Application:

F-16 a, b, c, d support equipment

Electrical Connection Type:

Bnc

Accessory Controlling Agency:

Any acceptable

Internal Battery Accommodation:

Not included

Voltage Rating:

115.0 volts or 230.0 volts

Electrical Connection Quantity:

2

Accessory Component Name:

Any acceptable

Measurement Type:

Frequency and ratio and period average

Frequency Range:

+0.100/+50.000 megahertz multiple period and +0.000/+10.000 megahertz multiple period and +0.000/+1.000 megahertz multiple period and +0.000/+1.000 megahertz multiple period and +0.000/+0.300 megahertz multiple period

Accuracy Rating:

Porm 1 count porm 1 count of f1, porm trigger error of f2 porm 1 count and porm trigger error

Gate Time:

10.0 seconds

Sensitivity Rating:

Any acceptable

Ratio Display:

F1/f2 times period multiplier

Period Range:

+1.0/+100000.0

Internal Calibration Feature:

Included

Display Type:

Any acceptable

Display Units Indicator:

Not included

Display Positioned Decimal Point:

Not provided

Display Storage Facility:

Included

Remote Control Provisions:

Not included

Solid State Feature:

Not included

Inclosure Material And Location:

Metal case

Inclosure Surface Treatment And Location:

Enamel case

Plug-in Units Provision:

Included

Standard Frequency Output Feature:

Included

Phase:

Single

Specification Or Standard:

4 type

Fsc Application Data:

Counter type indicators, test, digital display

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T297-a