

View Online at <https://aerobasegroup.com/nsn/6625-00-914-4128>

Circuit Current For Which Designed:

Dc

Overall Length:

2.188 inches

Overall Height:

Between 2.781 inches and

Overall Width:

Between 3.469 inches and 3.531 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.000 inches

Meter Body Width Behind Mounting Flange:

3.344 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 bracket

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+5.0 amperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

1.860 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-d-70327

Style Designator:

Rectangular flush mtg

Supplementary Features:

Hardware brightly plated

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0