

View Online at <https://aerobasegroup.com/nsn/6625-00-914-8867>

Circuit Current For Which Designed:

Ac

Overall Length:

3.080 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches

Overall Height:

2.500 inches

Overall Width:

2.680 inches

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Nut 4; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator 2nd range and red single indicator 2nd range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.188 inches

Meter Body Diameter Behind Mounting Flange:

2.250 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Buff single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-20.0/+3.0 voice units single indicator 2nd range

Mounting Stud Diameter:

0.115 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug and 2 threaded hole

Special Features:

Plus and minus signs on rear of case

Special Markings:

Voice units range 0 to + 3 is red

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0