## NSN 6625-00-915-1643

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-915-1643

**Circuit Current For Which Designed:** 

Dc

**Dielectric Withstanding Voltage In Volts:** 

1500.0

**Overall Length:** 

1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.306 inches and 1.318 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

Between 1.306 inches and 1.318 inches

**Overall Height:** 

Between 1.734 inches and 1.766 inches

**Overall Width:** 

Between 1.734 inches and 1.766 inches

**Mounting Hole Diameter:** 

0.125 inches

**Scale Division Quantity:** 

50 single indicator single range

**Environmental Protection:** 

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:** 

Washers 4, nuts 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

**Mounting Arrangement Style:** 

Four hole/stud rectangular/square

**Sensitivity Rating:** 

0.9 ohms

**Dial Scale Marking Color:** 

Black single indicator single range

**Accuracy In Percent:** 

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.000 inches

**Meter Body Diameter Behind Mounting Flange:** 

1.510 inches

**Movement Type:** 

Moving coil, permanent magnet

**Background Color:** 

White single indicator single range

## NSN 6625-00-915-1643

Ammeter - Page 2 of 2



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+50.0 milliamperes, dc single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 solderless lug
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0