NSN 6625-00-920-4263

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-920-4263

View Online at https://aerobasegroup.com/nsn/6625-00-920-4263
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
4.625 inches
Mounting Hole Diameter:
0.125 inches
Overall Diameter:
2.695 inches
Environmental Protection:
Submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+380.000/+420.000 hertz
Dial Scale Marking Color:
Black, federal standard 595, 27038 single indicator single range
Accuracy In Percent:
-0.6/+0.6 at 1/2 scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black, federal standard 595, 27038 single indicator single range

Scale Marking:

2 bands marked bad and 1 marked good

NSN 6625-00-920-4263

Arbitrary Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Features Provided:
Rfi shielding
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized; error in freq indication shall not exceed porm 2.4 hz
Special Markings:
Bands marked bad from 375 to 380 hz and from 420 to 425 hz, good band from 380 to 420 hz deflections
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Style Designator:
Round flush mtg
Supplementary Features:
Input limits 103.5 to 126.5 vac rms without exceeding initial accuracy; attenuation due to conductive coating of window shall be 80 db min at
3 mhz
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0