

View Online at <https://aerobasegroup.com/nsn/6625-00-922-3586>

Overall Length:

18.375 inches

Wattage Rating In Watts:

95.0

Overall Height:

5.219 inches

Overall Width:

16.375 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Accessory Component Quantity:

3

Electrical Connection Type:

Bnc

Accessory Controlling Agency:

Hewlett-packard co

Accessory Identifying Number:

Cg-409e/u type no. And 05245-6022 part no. And 5243a44a part no.

Internal Battery Accommodation:

Not included

Voltage Rating:

115.0 volts or 230.0 volts

Output Frequency Rating:

5.0 megahertz

Electrical Connection Quantity:

7

Mounting Method:

Case

Accessory Component Name:

Cable assembly, rf; circuit board extender; rack mounting kit

Measurement Type:

Frequency and period average and ratio

Frequency Range:

+0.000/+50.000 megahertz

Accuracy Rating:

Porm 1 count; porm time base

Gate Time:

Between 1.0 microseconds and 10.0 seconds

Sensitivity Rating:

0.1 v rms each input max

Ratio Display:

F1/f2 times period multiplier

Period Range:

+0.1/+100000.0

Period Range Step Quantity:

6 unit steps

Count Rate:

0.0 megahertz single period and 1.0 megahertz single period

Internal Calibration Feature:

Included

Display Type:

Numeric readout tube

Display Digit Quantity:

8

Display Units Indicator:

Included

Display Positioned Decimal Point:

Provided

Display Storage Facility:

Included

Remote Control Provisions:

Included

Solid State Feature:

Included

Inclosure Material And Location:

Aluminum case

Inclosure Surface Treatment And Location:

Enamel case

Plug-in Units Provision:

Included

Standard Frequency Output Feature:

Included

Frequency Accuracy/stability:

3 parts per 1, 000, 000, 000 per day

Output Frequency Waveform:

Sinusoidal

Frequency Output Amplitude:

1.0 volts peak to peak

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T297-a