

View Online at <https://aerobasegroup.com/nsn/6625-00-922-5968>

Mounting Type:

Bench

Overall Length:

14.750 inches

Overall Height:

11.250 inches

Overall Width:

11.125 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 100.0 hertz

Case Material:

Aluminum

Case Surface Treatment:

Enameled

Frequency Range Rating:

+0.010/+50.000 megahertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds; jetds; jetds; jetds; jetds; jetds; jetds

Accessory Identifying Number:

Cn-223/urm-25j type no. And cn-224/urm-25j type no. And sm-35/urm-25 type no. And cx-1363/u type no. And cg-409/u/4ft2in. Type no. And cg-409/g/6in. Type no. And ug-684a/u type no.

Joint Electronics Type Designation System Item Name:

Generator, signal

Joint Electronics Type Designation System Item Type Number:

Type no. Amurm25jwspares

Internal Battery Accommodation:

Not included

Output Impedance Rating:

0.5 kilohms and 50.0 kilohms

Voltage Rating:

115.0 volts

Frequency Band Quantity:

9

Modulation Type:

Am

Accessory Component Name:

Fixed attenuator 1; fixed attenuator 1; antenna simulator 1; lead, test 1; cord 1; cord 1; connector, adapter 1

Calibration Accuracy Rating:

Porm 0.5 pct to 1 mhz; porm0.05 pct 1 mhz to 50 mhz

Crystal Controlled Feature:

Not provided

Calibrated Signal Output Range:

0.1 uv to 0.1 v

Maximum Signal Output:

0.1v maximum signal output

Signal Output Constancy:

Porm 10 pct maximum variation throughout freq range

Modulator Location:

External

Modulated Frequency Rating:

Between 0.010 kilohertz and 15.0 kilohertz

Modulation Degree:

50.0 percent

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-j