

View Online at <https://aerobasegroup.com/nsn/6625-00-923-9022>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

2.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.040 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.670 inches

Overall Height:

3.940 inches

Overall Width:

4.250 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Nut 12; flat washer 8; lockwasher 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.120 inches

Meter Body Diameter Behind Mounting Flange:

3.250 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+500.0 milliamperes, dc single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 4 threaded stud

Operating Voltage Rating In Volts:

6.0 dc

Special Features:

2 of 4 terminals used for lamps

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0