

View Online at <https://aerobasegroup.com/nsn/6625-00-924-0328>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

1.220 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

Mounting Hole Diameter:

0.190 inches

Distance Between Mounting Facility Centers:

2.060 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.630 inches

Meter Body Width Behind Mounting Flange:

2.380 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+5.0 amperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

1.780 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0