

View Online at <https://aerobasegroup.com/nsn/6625-00-930-5846>

Circuit Current For Which Designed:

Ac

Overall Length:

2.449 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.728 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.367 inches

Overall Height:

3.510 inches

Overall Width:

3.508 inches

Mounting Stud Length:

0.500 inches

Environmental Protection:

Dust resistant and fungus resistant and shock resistant and vibration resistant and water resistant

Shortest Horizontal Distance Between Mounting Centers:

2.367 inches

Furnished Items And Quantity:

Nut 5; flat washer 5; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Sensitivity Rating:

5.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.289 inches

Meter Body Diameter Behind Mounting Flange:

2.837 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+250.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0