## NSN 6625-00-930-5846

Ammeter - Page 1 of 2

Black single indicator single range



View Online at https://aerobasegroup.com/nsn/6625-00-930-5846

Circuit Current For Which Designed:
Ac
Overall Length:
2.449 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.728 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.367 inches
Overall Height:
3.510 inches
Overall Width:
3.508 inches
Mounting Stud Length:
0.500 inches
Environmental Protection:
Dust resistant and fungus resistant and shock resistant and vibration resistant and water resistant
Shortest Horizontal Distance Between Mounting Centers:
2.367 inches
Furnished Items And Quantity:
Nut 5; flat washer 5; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud triangular
Sensitivity Rating:
5.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.289 inches
Meter Body Diameter Behind Mounting Flange:
2.837 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:

## NSN 6625-00-930-5846

Ammeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
3 threaded stud
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0/+250.0 amperes, ac single indicator single range
Mounting Stud Diameter:
0.138 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Chromate
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0