

View Online at <https://aerobasegroup.com/nsn/6625-00-930-9205>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 1.540 inches and 1.620 inches

Overall Height:

1.832 inches

Overall Width:

1.832 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.375 inches

Distance Between Mounting Facility Centers:

1.855 inches

Furnished Items And Quantity:

Washer 2; hexnut 2; lockwasher 2; stop-nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 0.990 inches and 1.010 inches

Meter Body Diameter Behind Mounting Flange:

1.700 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

1 threaded body and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+6.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Internal shunting and knife edge pointer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0