

View Online at <https://aerobasegroup.com/nsn/6625-00-933-1252>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 2.110 inches and 2.140 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches

Overall Height:

2.650 inches

Overall Width:

2.650 inches

Mounting Hole Diameter:

0.168 inches

Scale Division Quantity:

30 single indicator single range

Furnished Items And Quantity:

Term. Hdw 2; shunt 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 1.595 inches and 1.640 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.235 inches and 2.255 inches

Movement Type:

Electrodynamometer

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+30.0 amperes single indicator single range

Features Provided:

External shunting and luminous scale marking

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Shunt: 50 mv, 30 amp

Special Markings:

Prop amps; green band from 14 to 18 amps

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0